

# SAFETY DATA SHEET

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

B gel black

Product no.

00.594

**REACH registration number** 

Not applicable

Other means of identification

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

Black cyanacrylat filler

Uses advised against

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

#### Company and address

**HBC System Smarttool Production ApS** 

Hobrovej 961-963

9530 Stövring

Denmark

tel:+45 70 22 70 70

#### Contact person

Vibeke Jørgensen

info@hbc-system.com SDS date

### 28-08-2013

### **SDS Version**

2.0

### 1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Skin Irrit. 2, Eye Irrit. 2, STOT SE 3 // H335, H319, H315

See full text of H/R-phrases in section 2.2.

### **DPD/DSD Classification**

Irritant. (Xi).

Irritating to eyes, respiratory system and skin.(R36/37/38).

#### 2.2. Label elements

### Hazard pictogram(s)





### Signal word

Warning!

### Hazard statement(s)

Causes skin irritation. (H315)

Causes serious eye irritation. (H319) May cause respiratory irritation. (H335)

#### Identity of the substances primarily responsible for the major health hazards

Ethyl 2-cyanoacrylate

General

Prevention Wear protective gloves/protective clothing/eye protection/face protection.

(P280)

Wash exposed areas thoroughly after handling. (P264)

Safety statement(s)

Response If eye irritation persists: Get medical advice/attention. (P337+P313)

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

(P305+P351+P338)

Storage Store locked up. (P405)

Disposal Dispose of contents/container to an approved waste disposal plant.

(P501)

#### 2.3. Other hazards

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

### **▼**Additional labelling

Cyanoacrylate. Danger. Bonds to skin and eyes in seconds. Keep out of reach of children.

#### Additional warnings

voc

VOC

#### **SECTION 3: Composition/information on ingredients**

#### **▼**3.1/3.2. Substances

NAME: Ethyl 2-cyanoacrylate

IDENTIFICATION NOS.: CAS-no: 7085-85-0 EC-no: 230-391-5 Index-no: 607-236-00-9

CONTENT: 90-95% DSD CLASSIFICATION: Xi; R36/37/38

CLP CLASSIFICATION: Skin Irrit. 2, Eye Irrit. 2, STOT SE 3

H315, H319, H335

NOTE: S

(\*) See full text of H/R-phrases in chapter 16. Occupational limits are listed in section 8, if these are available. S = Organic solvent

#### Other informations

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

### Inhalation

Get the person into fresh air and stay with them.

### Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.



### Eye contact

Remove contact lenses. Flush eyes with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Contact a doctor at once.

#### Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

#### **Burns**

Rinse with water until the pain stops and continue for 30 minutes.

### **▼4.2. Most important symptoms and effects, both acute and delayed**

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

### 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

### Information to medics

Bring this safety data sheet.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Nitrogen oxides. Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material.

### 6.2. Environmental precautions

No specific requirements.

## 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

#### 6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Smoking, consumption of food or liquid, and storage of tobacco, food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.



### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Storage temperature

Room temperature 18 to 23°C

### 7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

#### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters



Ethyl 2-cyanoacrylate (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): - ppm | - mg/m3

Short-term exposure limit (15-minute reference period): 0.3 ppm | 1.5 mg/m3

#### **DNEL / PNEC**

No data available.

#### 8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

#### **General recommendations**

Smoking, consumption of food or liquid, and storage of tobacco, food or liquid, are not allowed in the workroom.

#### **Exposure scenarios**

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

#### **Exposure limits**

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

### Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

#### Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment



### Generally

Only CE-marked personal protection equipment should be used.

#### Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

### Skin protection

Special work clothing should be used.

### **Hand protection**

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.



### Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

### **SECTION 9: Physical and chemical properties**

 $\nabla$ 9.1. Information on basic physical and chemical properties

Form Colour Odour pH Viscosity Density (g/cm3)

Gel Black Sharp/pungent - - 1,

Phase changes

Melting point (°C) Boiling point (°C) Vapour pressure (mm Hg)

>150

Data on fire and explosion hazards

Flashpoint (°C) Ignition (°C) Self ignition (°C)

>85 - -

Explosion limits (Vol %) Oxidizing properties

Solubility
Solubility in water n-octanol/water coefficient

Soluble -

9.2. Other information

Solubility in fat Additional information

- N/A

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

### 10.3. Possibility of hazardous reactions

No special

### 10.4. Conditions to avoid

No special

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidising agents, and strong catabolic agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

**▼**Acute toxicity

Substance Species Test Route of exposure Result Ethyl 2-cyanoacrylate Rat LD50 Oral 5 mL/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

No data available.

### Germ cell mutagenicity

No data available.

## Carcinogenicity

No data available.

#### Reproductive toxicity

No data available.

#### STOT-single exposure

May cause respiratory irritation.



#### STOT-repeated exposure

No data available.

### **Aspiration hazard**

No data available.

### **▼**Long term effects

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

### **SECTION 12: Ecological information**

#### ▼12.1. Toxicity

Substance Species Test Test duration Result

No data available.

### 12.2. Persistence and degradability

Substance Biodegradability Test Result

No data available.

#### 12.3. Bioaccumulative potential

Substance Potential bioaccumulation LogPow BFC

No data available.

### ▼ 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

No data available

#### 12.6. Other adverse effects

No special

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

### Waste

EWC code

08 04 09

#### Specific labelling

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

#### **SECTION 14: Transport information**

Not listed as dangerous goods under ADR and IMDG regulations.

#### 14.1 – 14.4

ADR/RID	14.1. UN	14.2. UN proper shipping	14.3. Transport nazard	14.4. Packing	Notes
	number	name	class(es)	group	

IMDG UN-no. Proper Shipping Name Class PG\* EmS MP\*\* Hazardous constituent

#### 14.5. Environmental hazards

### 14.6. Special precautions for user

-



### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. For exceptions, see the Danish Working Environment Authority's Executive Order No. 239 of 6 April 2005. Must not be used by persons suffering acrylic dermatitis.

### **Demands for specific education**

Additional information

15.2. Chemical safety assessment

No

#### **SECTION 16: Other information'**

#### **Sources**

EC regulation 1907/2006 (REACH) Directive 2000/532/EC EC Regulation 1272/2008 (CLP)

### VFull text of H/R-phrases as mentioned in section 3

R36/37/38 - Irritating to eyes, respiratory system and skin.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

### The full text of identified uses as mentioned in section 1

Other symbols mentioned in section 2

### Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

### The safety data sheet is validated by

AW /CHYMEIA

Date of last essential change (First cipher in SDS version)

27-06-2013

Date of last minor change (Last cipher in SDS version)

28-08-2013

ALPHAOMEGA. Licens nr.:2603245129, HBC SYSTEM Danmark www.chymeia.com